

	FINISHED PRODUCT SPECIFICATION			Page No.	1 of 2
	Quality Control Department				
Product Name	NOVOMIX MR(AQ)-37131				
Colour	Brown				
Specification No.	FP/NOVOMPS/MR(AQ)-37131/01	Supersedes No.	NA		
Reference	In House	Effective Date	06/06/2025		
Ref. Annexure No.	A/SOP/QC/030/04	Review Month	May 2030		

GENERAL INFORMATION


Pharmacopoeial reference : In House

Quantity to be sampled :

Analysis Sample	Control sample
40 g	80 g

Shelf Life : 36 Months

Storage : Store in dry place, in well closed container, away from direct heat and light.

	PREPARED BY	REVIEWED BY	APPROVED BY
Name	Prashant Patil	Rajanikant Audhkar	Manish Mahajan
Sign/Date	 06/06/25	 06/06/25	 06/06/2025
Designation	QC officer	SO, Executive	Manager
Department	Quality Control	Quality control	Quality Assurance

	FINISHED PRODUCT SPECIFICATION		Page No.	2 of 2
	Quality Control Department			
Product Name	NOVOMIX MR(AQ)-37131			
Specification No.	FP/NOVOMPS/MR(AQ)-37131/01			

Qualitative Formula :

1. Polyvinyl Alcohol USP
2. Lecithin USP
3. Polyethylene Glycol USP
4. Talc USP
5. Titanium Dioxide USP
6. Red Iron Oxide USP
7. Black Iron Oxide USP

Sr. No.	Test	Specification	Reference
1.	Appearance	Brown powder	GTP/QC/001
2.	Identification by IR	IR spectrum of test sample should be concordant with the IR spectrum of standard.	GTP/QC/009
3.	Colour Shade	Colour shade should match visually with Standard	GTP/QC/008
4.	Particle Size (Done on wet slurry)	Not less than 99.00 % w/w passes through 100 mesh	GTP/QC/006
5.	Tapped Density	Not more than 1.2 g/ml	GTP/QC/003
6.	Ash Content	Not more than 45 % w/w	GTP/QC/004

REVISION HISTORY FOR SPECIFICATION:

Revision No.	Revision Description	Effective Date
01	New Document	06/06/2025

	PREPARED BY	REVIEWED BY	APPROVED BY
Sign/Date	<i>Getal</i> 06/06/25	<i>Rmudra</i> 06/06/25	<i>AB</i> 06/06/2025



	FINISHED PRODUCT STANDARD TEST PROCEDURE (STP)			Page No.	1 of 4
	Quality Control Department				
Product Name	NOVOMIX MR(AQ)-37131				
Colour	Brown				
STP No.	FP/NOVOMSTP/ MR(AQ)-37131/01				
Reference	In House	Supersedes No.	NA		
Ref. SPEC No.	FP/NOVOMPS/MR(AQ)-37131/01	Effective Date	06/06/2025		
Ref. Annexure No.	A/SOP/QC/030/08	Review Month	May'2030		

01.	Appearance : Instrument: Balance Take about 2 to 3 g of test sample and transferred into a clean and dry petri dish. Spread it uniformly by spatula and observe. Specification: Brown powder.
02.	Identification by IR: Instrument : Balance , IR Spectrophotometer, Oven Take about 1 mg of sample to be analyzed and 100 mg IR grade KBr onto piece of weighing paper. The KBr should be store in the desiccator when not in used. Transfer the sample /KBr mixture to the agate mortar. Thoroughly disperse the mixture using the spatula or spoon. The pestle is then used with a grinding motion to homogenously disperse the mixture component. Completed homogeneity takes approximately 1-2 minutes of grinding the components with the pestle. Prepare a KBr pellet using an appropriate apparatus (Press Kit, E- Z press etc.) carefully examine the pallet film to ensure that it is intact and somewhat transparent. Run the pallet on suitable spectrophotometer from 4000 cm^{-1} to 650 cm^{-1} according to the operating instruments. All peak should be match the reference with relation to wavelength location and approximate magnitude location. Overlap the sample spectra with reference spectra. Note: Sample and KBr to be dried at 105°C for about 30 minutes before use Or

	PREPARED BY	REVIEWED BY	APPROVED BY
Name	Prashant Patil	Rajanikant oudhkar	Manish Mahajan
Sign/Date	<i>Patil</i> 06/06/25	<i>Roudik</i> 06/06/25	<i>Manish Mahajan</i> 06/06/2025
Designation	Qc.officer	ss.Executive	Manager
Department	Quality Control	Quality control	Quality Assurance

	FINISHED PRODUCT STANDARD TEST PROCEDURE (STP)		Page No.	2 of 4
	Quality Control Department			
Product Name	NOVOMIX MR(AQ)-37131			
STP No.	FP/NOVOMSTP/ MR(AQ)-37131/01			

	By ATR Accessory: Make sure the crystal is free from any residue by wiping clean with IPA or methanol and delicate wipe. Perform the background measurement. Grind a small amount of sample using agate mortar. Transfer enough of the undiluted sample to completely cover the crystal. Lower the ATR press all the way down with sufficient pressure to ensure a well-defined scan. Collect a spectrum of sample from 4000 cm⁻¹ to 650 cm⁻¹. All peak should be match the reference with relation to wavelength location and approximate magnitude location. Overlap the sample spectra with reference spectra. Specification: IR spectrum of test sample should be concordant with the IR spectrum of standard.
03.	Colour Shade : Compare the colour shade of tablets coated with sample, visually with reference standard tablets. Specification: Colour shade should match visually with Standard.
04.	Particle Size (Done on wet slurry): Instrument: Balance, Stirrer, Oven Prepare about 5% dispersion (5 g in 95 g ± 1 g of distilled water) and stir the dispersion for about 45 minutes with constant stirring. Pour this dispersion on the top of the 100 mesh tarred mesh in a form of fine stream. Sieve the remaining particles on the mesh without applying any pressure with the help of running water. Continue the wet sieving process until the emerging liquid appears free of particles. Remove the mesh and dry it at 105°C. Allow the mesh to come to room temperature in a desiccator before weighing. Repeat the operation until two successive weighing do not differ by more than 1 mg. Determine the weight of dried material on the mesh. Calculation: Percentage w/w passed through 100 mesh = $\frac{100 \times W1 - W5}{W1}$ Where, W1 = Weight of sample in g taken for mesh test.

	PREPARED BY	REVIEWED BY	APPROVED BY
Sign/Date	 06/06/25	 06/06/25	 06/06/25

	FINISHED PRODUCT STANDARD TEST PROCEDURE (STP)		Page No.	3 of 4
	Quality Control Department			
Product Name	NOVOMIX MR(AQ)-37131			
STP No.	FP/NOVOMSTP/ MR(AQ)-37131/01			

W2 = Weight of empty mesh

W3 = Weight of mesh plus residue after drying

W4 = Weight of mesh plus residue after drying (constant weight)

W5 = Weight of material remained on the mesh after drying to constant weight
= W4 - W2

Specification: Not less than 99.00 % w/w passes through 100 mesh.

05. Tapped Density:

Instrument: Balance, Densitometer

Weigh 10 g of sample. Pour it in a 50 ml Graduated measuring cylinder. Set 100 taps for the densitometer. Note the volume (A) occupied by 10 g of the powder after 100 taps on the graduated cylinder.

Calculations: Tapped Density in g/ml = $\frac{\text{Weight of sample}}{\text{Volume A}}$

Specification : Not more than 1.2 g/ml

06. Ash Content :

Instrument: Balance, Muffle Furnace

Heat a silica crucible at $600 \pm 25^\circ \text{C}$ for 15 minutes, allow to cool in a desiccator and weigh. Take 1-2 g of sample to the crucible and weigh the crucible. Ignite the sample at $600 \pm 25^\circ \text{C}$ for 45 minutes. Allow the silica crucible to come to room temperature in a desiccator before weighing.

Repeat the operation until two successive weighing do not differ by more than 0.5 mg

Calculation:

$$\% \text{ Ash} = \frac{(W4 - W1)}{(W2 - W1)} \times 100$$



Where, W1 = Weight of the empty crucible (g)

W2 = Weight of the crucible with test sample before ignition (g)

W3 = Weight of the crucible with residue after ignition (g)

W4 = Weight of the crucible with residue after ignition (g) (Constant weight)




Specification: Not more than 45 % w/w.

	PREPARED BY	REVIEWED BY	APPROVED BY
Sign/Date	 06/06/25	 06/06/25	 06/06/2025

	FINISHED PRODUCT STANDARD TEST PROCEDURE (STP)	Page No.	4 of 4
	Quality Control Department		
Product Name	NOVOMIX MR(AQ)-37131		
STP No.	FP/NOVOMSTP/ MR(AQ)-37131/01		

REVISION HISTORY FOR STANDARD TEST PROCEDURE:

Revision No.	Revision Description	Effective Date
01	New Document	06/06/2025

	PREPARED BY	REVIEWED BY	APPROVED BY
Sign/Date	 06/06/25	 06/06/25	 06/06/2025